

Specifications Cordstrap Composite Strapping Solution: CC85 & CB8

Performance Specifications	
Performance System (strap & buckle) System Breaking Strength*	1250 daN / 2810 lbf
Performance Strap Linear Breaking Strength*	780 daN / 1755 lbf
Elongation	<7%
Elongation at Break	11% - 17%
Certification	German Lloyd

Strap Specifications	
Dimensions Width* Thickness*	25 mm / 1" 0,97 mm / 1/32"
Material	High tenacity polyester filament yarn and Homopolymer Polypropylene
Coil Length per Coil** Core Diameter	500 m / 1640 ft 200 mm / 8"
Packaging Carton Box Dimensions* Box Weight* Product Code	2 coils per box 390 x 390 x 354 mm / 15.3/8" x 15.3/8" x 14" 25 kg / 55 lbs 7257000
Pallet Box Dimensions* Box Weight* Product Code	30 coils per box 1181 x 781 x 890 mm / 46.9" x 31.1" x 35" 370 kg / 816 lbs 7257900

Buckle Specifications	
Dimensions Width*	25 mm / 1"
Material	Galvanized steel wire
Packaging Carton Box** Dimensions* Box Weight* Product Code	250 pieces per box 266 x 166 x 202 mm / 10.1/2" x 6.5/8" x 7.7/8" 14 kg / 31 lbs 7360500



Represented in over 50 countries

World market leader
ISO 9001:2008 certified
Manufacturer & supplier since 1965
Offering genuine customer solutions

Specialist advice
Continued product development
Training at Cordstrap Training Centers
Quality assurance

Recommended Tensioner(s)	
Manual Tensioner Applied Pre-tension Suitable for strap widths Suitable for strap thicknesses Weight* Product Code	CT40 (2) 200 – 800 daN / 450 – 1800 lbf 19 mm - 40 mm / 3/4" – 1.5/8" 0,6 - 1,5 mm / 1/32"- 1/16" 2,5 kg / 5.5 lbs 7502400
Manual Tensioner Applied Pre-tension Suitable for strap widths Suitable for strap thicknesses Weight* Product Code	CTT40 200 – 800 daN / 450 – 1800 lbf 19 mm - 40 mm / 3/4" – 1.5/8" 0,6 - 1,8 mm / 1/32"- 5/64" 2,5 kg / 5.5 lbs 7502500

Accessories	
Coil Dispenser with Buckle Tray Product Code Portable Version Product Code Static Version	7538000 7544000
Edge Protection	Different types and sizes available. Your Cordstrap cargo securing specialist can advise you about the best Edge Protection for your application.
Pallet Needle Product Code	7551000

* Tolerance of +/- 10%

** Tolerance of +/- 2%

We recommend storing all Cordstrap Products in a cool a dry environment out of direct sunlight and between -5°C and 40°C / 23°F and 104°F

All information provided is based on accuracy at time of creation



Represented in over 50 countries

World market leader

ISO 9001:2008 certified

Manufacturer & supplier since 1965

Offering genuine customer solutions

Specialist advice

Continued product development

Training at Cordstrap Training Centers

Quality assurance